

SAFETY DATA SHEETS (SDS)

71743

SECTION 1 - PRODUCT AND COMPANY IDENTIFICATION

| Product Name: | Quick Change Sandin Resin Fiber Discs, San | • | ace Conditioning Discs, Flap Discs, |
|--------------------|---|--------------|-------------------------------------|
| Forney SKUs: | 71743, 71745, 71746 | , 71748 | |
| | | | |
| Manufacturer Name: | Forney Industries, Inc | 2. | |
| Address: | 2057 Vermont Drive, | Fort Collins | , CO 80525 |
| Website: | www.forneyind.com | | |
| Email: | customerservice@for | rneyind.com | <u>1</u> |
| Phone Number: | 800-521-6038 | | |
| Fax Number: | 970-498-9505 | | |
| SDS Creation Date: | April 1st. 2014 | Revised: | 12/15/2016 Rev.: 2.1 |

SECTION 2 - HAZARDS IDENTIFICATION

| Inhalation, Acute: | Dust Inhalation may cause coughing, shortness of breath or irritation. |
|------------------------|--|
| Inhalation, Chronic: | Dust Inhalation may affect breathing capacity. |
| Ingestion: | No known adverse effects, but ingestion not recommended. |
| Skin: | Not absorbed through skin. Dust may cause irritation/rash to some. |
| Eye: | Dust may irritate eyes. |
| Other Potential Risks: | Grinding may create elevated sound levels, which may affect |
| | hearing and may aggravate pre-existing respiratory condition. |

SECTION 3 - COMPOSITION/INFORMATION ON INGREDIENTS

| | INGREDIENTS & CHEMICAL IDENTITY (COMMON NAME): | CAS # | % |
|---|--|------------|-------|
| 1 | * Nylon | 63428-83-1 | 5-25% |
| 2 | * Aluminum Oxide (Alumina) | 1344-28-1 | 0-65% |
| 3 | * Silicon Carbide (Crystolon) | 409-21-2 | 0-65% |
| 4 | * Phenol Formaldehyde (Phenolic Resin) | N/A | 0-35% |
| 5 | * Polyurethane (Resin Cured) | N/A | 0-35% |

SECTION 4 - FIRST AID MEASURES

| Eye Contact: | Immediately flush eyes with water for at least 15 to 20 minutes. |
|---------------|---|
| | Make sure the dust is completely washed off. |
| | Get medical attention, if irritation symptoms develop or persist. |
| Skin Contact: | Wash skin with soap and rinse plenty of water. Get medical attention if |
| | irritation symptoms develop or persist. |
| Inhalation: | Remove affected person to fresh air. Apply artificial respiration if necessary. |
| | Seek medical assistant if affected person is still having trouble breathing. |
| Ingestion: | Unlikely to occur, but accidentally ingested, continue monitoring person |
| | for several days to make sure any symptoms persist. Contact physician if any symptom(s) occurred. |
| | |

SECTION 5 - FIRE FIGHTING MEASURES

| Flammable Property: | Non-flammable |
|----------------------|--------------------|
| Flash Point: | N/A |
| Flammable limit: | N/A |
| LEL: | N/A |
| UEL: | N/A |
| Extinguishing Media: | Extinguisher/Water |
| | |

SECTION 6 - ACCIDENTAL RELEASE MEASURES

| Step to be taken in case | |
|--------------------------|---|
| of leaks or spills: | Ventilate Area. Normal clean-up procedures. |
| | Avoid creating dusty conditions |
| Waste disposal method: | Dispose-of in a secured sanitary landfill consistent with applicable Federal, State and Local Laws and Regulations |

SECTION 7 - HANDLING AND STORAGE

| Handling: | Handle with adequate ventilation (See OSHA 29CFR 1910.94 Ventilation) |
|----------------------------|---|
| | and 29CFR 1910.1000 (Air Contaminates) |
| Storage: | Store in dry area, away from heat source. |
| | Ideal storage temperature 65-70°F (18-24°C), 50-60% RM |
| General Hygiene Practices: | Wear proper gloves, eye and face protection |

SECTION 8 - EXPOSURE CONTROL / PERSONAL PROTECTION

| | INGREDIENTS & CHEMICAL IDENTITY (COMMON NAME): | OSHA PEL | ACGIH TLV | OTHER LIMIT |
|---|--|-----------------|----------------|-----------------|
| 1 | * Nylon | Non-established | Non-establised | Non-established |
| 2 | * Aluminum Oxide (Alumina) | 15 mg/m3 | 10 mg/m3 | Non-established |
| 3 | * Silicon Carbide (Crystolon) | 15 mg/m3 | 10 mg/m3 | Non-established |
| 4 | * Phenol Formaldehyde (Phenolic Resin) | Non-established | Non-establised | Non-established |
| 5 | * Polyurethane (Resin Cured) | Non-established | Non-establised | Non-established |

| Repiratory Protection: | Specify Type, as needed. For Approved Dust Respirators, See OSHA 29CFR 1910.134 |
|---------------------------|--|
| Eye and Face Protection: | Always wear safety glasses. Recommended - See OSHA 29 CFR 1910.133 and ANSI Z87.1 |
| Hearing Protection: | Hearing Protection as needed. OSHA 29CFR 1910.95 |
| Skin and Hand Protection: | Wear glove and Lab coat |
| Local Exhaust : | Required to keep dust levels below permissible exposure limits |
| Mechanical: | Required to keep dust levels below permissible exposure limits |

SECTION 9 - PHYSICAL and CHEMICAL PROPERTIES

| Physical Sate Appreance: | Solid | Melting Point: | N/A |
|--------------------------|--------------|----------------------------|----------------|
| Flammability: | Non-flamable | Solubility: | insoluble |
| Ordor: | Odorless | Initial Boining Point: | N/A |
| Vapor Pressure: | N/A | Flash Point: | N/A |
| Vapor desity: | N/A | Evaporation Rate: | N/A |
| pH: | N/A | Auto-ignition tempurature: | Not determimed |
| Relative density: | N/A | Decomposition Tempurature | |
| | | & viscosity: | N/A |

SECTION 10 - STABILITY and REACTIVITY

| Hazardous Polymerization: | Hazardous polymerization does not occur under normal condition and usage |
|---------------------------|---|
| Stability: | Stable under normal condition |
| Condition to avoid: | Unspecified |
| Hazarous decompositon: | Dust from grinding could contain ingredients listed in seciton 3 and other, potentially more hazardous components of the base material being ground or coatings applied to the base material. |

SECTION 11 - TOXICOLOGICAL INFORMATION

| Acute Toxicity: | This product has not been tested for its toxicity |
|------------------------|--|
| Ingestion: | If accidentally ingested, contact physician for medical attention. |
| Inhalation: | Dust inhalation may cause coughing, shortness of breath or irritation. |
| Skin: | Not absorbed through skin. Dust may cause irritation/rash to some. |
| Eye: | Dust may irritate eyes. |
| Other Potential Risks: | Grinding may create elevated sound levels, which may affect. |
| | hearing and may aggravate pre-existing respiratory condition. |
| Carcinogenicity: | Silica, Amorphous, Fused - IARC-3, NIOSE-X LD50/LC50 |
| | Values are not appropriate or available |

SECTION 12 - ECOLOGICAL INFORMATION

| Ecotoxicity: | No ecotoxicity data was found for the product. |
|------------------------|--|
| Environmental effects: | No known significant effects or hazards. |

SECTION 13 - DISPOSAL CONSIDERATIONS

| Waste Disposal Method: | Dispose-of in a secured sanitary landfill consistent with applicable |
|------------------------|--|
| | Federal, State and Local Laws and Regulations. |

SECTION 14 - TRANSPORT INFORMATION

| DOT Shipping Name: | Not regulated as hazadous material for transportation. |
|-------------------------|--|
| DOT UN Number: | Not regulated as hazadous material for transportation. |
| Transport hazard class: | None |
| Packing Group Number: | None |
| Environmental Hazard: | Not regulated as hazadous material for transportation. |
| label Required: | None |

SECTION 15 - REGULATORY INFORMATION

| SECTION 15 - REGULATORY IN | FORMATION |
|--|---|
| HCS Classification: U.S. Federal Regulations: | This product is Exampted from the regulatory requirement HCS SARA 311/312 Hazardous Substances: Not Applicable |
| | |
| | EPA TSCA Inventory: All of the ingrediennts are listed |
| | California Proposition 65: WARNING: Dust generated from cut, sand, drill or grind materials such as wood, paint, cement, masonry or metal when using |
| | this product offen contains chemicals known to cause cancer, birth defects, |
| | or other reproductive harm. |
| | Canadian WHMIS Classification: Not a controlled product. |
| | This product meets the definition of a "manufactured article" under the |
| | WHMIS regulations |
| | Canadian CEPA: None toxic substances. All of the ingredients are listed on |
| | the Canadian DSL. |

SECTION 16 - OTHER INFORMATION

Label Requirement:

Not controlled under O.S.H.A and under W.H.M.S. when used according to Industry safety standard.

